



บริษัท เอส.เค.โอ เอ เซ็นเตอร์ จำกัด (สาขา 00002)

เลขประจำตัวผู้เสียภาษีอากร 0655539000531

299 หมู่ที่ 2 ต.แม่เหิระ อ.เมือง จ.เชียงใหม่ 50100

เบอร์โทร 053 279-799 แฟกซ์ 053-271-786

ศูนย์บริการ - จำหน่าย - เครื่องใช้สำนักงานทุกชนิด " มาตรฐานการบริการสากล ISO 9001:2015 "

วิทยาลัยสารพัดช่างลำปาง

วันที่ 09.01.23

วันที่ 09.01.23

วันที่ 09.01.23

วันที่ 09.01.23

SKF-GA-006

ใบเสนอราคา

Quotation

เรียน ผู้อำนวยการ

หน่วยงาน วิทยาลัยสารพัดช่างลำปาง

ที่อยู่ 551 หมู่ 1 ต.พระบาท อ.เมือง จ.ลำปาง 52000

เลขประจำตัวผู้เสียภาษี 0994000435681

บุคคลที่ติดต่อ

โทรศัพท์ 054-821567

แฟกซ์ 054-821568

เลขที่ใบเสนอราคา SO076600025

วันที่ 13/01/2023


ส่งมอบ 30 วัน

ยื่นราคา 30 วัน

การชำระเงิน เครดิต / เครดิต 30 วัน

ประเภทราคา รวมภาษี

ที่	รายละเอียดสินค้า	จำนวน	หน่วยนับ	ราคา	รวมเงิน
1	เครื่องสแกนเนอร์ สำหรับงานเก็บเอกสารระดับศูนย์บริการ แบบที่ ๓ ยี่ห้อ Fujitsu รุ่น Image scanner fi-7160 สแกนเอกสารแนวนอนขนาด A4 ที่ 60 ppm / 120 ipm (200/300 dpi) และสามารถบรรจุกระดาษได้สูงสุด 80 แผ่นต่อครั้ง ความละเอียดในการสแกน 200/300/600 dpi เครื่องสแกนแบบ ADF (Automatic Document Feeder), Duplex ตัวป้อนเอกสารอัตโนมัติ 80 แผ่น รองรับขนาดเอกสาร A8-A4 การเชื่อมต่อ Interface USB 3.0 ขนาดเครื่อง 300 x 170 x 163 mm น้ำหนัก 4.2 kg รับประกันสินค้า 1 ปี	1	เครื่อง	34,900.00	34,900.00



หมายเหตุ : ราคาที่เสนอรวมภาษีมูลค่าเพิ่ม 7% แล้ว

กำหนดส่งมอบสินค้า 30 วัน, กำหนดยื่นราคา 30 วัน ราคาอาจเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

บริษัท เอส.เค.โอ.เอ.เซ็นเตอร์ จำกัด ขอขอบคุณท่านที่ให้ความสนใจผลิตภัณฑ์ที่เสนอราคา

และหวังเป็นอย่างยิ่งที่จะได้มีโอกาสบริการท่านในโอกาสต่อไป

ตัวอักษร : สามหมื่นสี่พันเก้าร้อยบาทถ้วน

รวมเป็นเงิน 34,900.00

หักส่วนลด

จำนวนเงินหลังหักส่วนลด 34,900.00

จำนวนเงินก่อนภาษี 32,616.82

จำนวนภาษีมูลค่าเพิ่ม 7 % 2,283.18

รวมเป็นเงินสุทธิ 34,900.00

กรุณาลงนามในส่วนของผู้ลูกค้าหลังจากพิจารณาต้องการสั่งซื้อสินค้าแล้วแฟกซ์กลับกับบริษัทฯ เพื่อเป็นการยืนยันเงื่อนไขราคา อีกครั้ง แฟกซ์ 053-271-786

ส่วนของผู้ลูกค้า ผู้อนุมัติ/ผู้เซ็นราคา

ลงนาม

ตำแหน่ง

วันที่



ผู้เสนอราคา

อดุลย์ พุทธิราช

()

โทร. 061-4139608

อีเมล skoa.sale@hotmail.com

จำนวน ๖๐๘.๖๙.๖๐ ๖๐ สังกัด บัณฑิต

Sho Fujitsu

6906280874

2021.09.20

☒ เพื่อโปรดทราบ

☒ เพื่อโปรดพิจารณา

☒ เห็นควรแจ้ง... ๑๐๘ ๑๒, ๑๓๑๒

☐ เห็นควรมอบ.....

8
and made

☒ เพื่อโปรดทราบ

☒ เพื่อโปรดพิจารณา

☒ เห็นควรแจ้ง... ๕๐๖, ๗๗, ๖๐๖, ๗๗

☐ เห็นควรมอบ.....

५२

(นายบุญฤทธิ์ กันมาเวียง)

รองผู้อำนวยการฝ่ายบริหารทรัพยากร

୧୯୫୩.୧୧.୫୭

☒ 1570 www.condition.com

☐ แจ้ง.....

☐ มอป.....

(นายวิชรุตติ ลิ้มจินดา)

ผู้อำนวยการวิทยาลัยสารพัดช่างลำปาง

182966

FUJITSU Image Scanner fi-7160

The fi Series entry ADF model scanner offers superior cost performance



- Best in its class in cost performance
- Large volume hopper
- Equipped with LCD
- Paper protection function by detecting paper jam sounds
- "Skew Reducer" - stable paper feeding mechanism
- Centralized management of multiple scanners
- Renewed scanner driver and image capturing software

Visit the fi Series homepage for ordering and purchasing information
<http://imagescanner.fujitsu.com/>

A4

Color
60
ppm*

Mono.
60
ppm*

DUPLEX

* A4 Portrait 200/300 dpi

■fi-7160 Features

■Best in its class in cost performance

The fi-7160 scans color A4 documents at a speed of 60 ppm / 120 ipm, offering unmatched cost-performance.

■Large volume hopper

The scanner is capable of setting up to 80 pages in the large volume hopper which allows you to quickly digitize a large volume of documents.

■High speed interface

The scanner supports USB3.0 for high speed data transfer between scanner and the computer.

■Equipped with LCD (Liquid Crystal Display)

LCD is equipped on the operational panel to display the operational settings for scanning documents, the number of sheets scanned, and error status. It is used to easily check the status of the scanner.

■Equipped with enhanced Paper protection function

The new technology iSOP (Intelligent Sonic Paper Protection) reduces the risk of having the documents damaged by stopping the scan when the scanner detects paper jam sound.

■"Skew Reducer" – stable paper feeding mechanism

The scanner is equipped with "Skew Reducer" to ensure straight paper feeding even for mix batch of small or thin papers. This function reduces the skewness of the documents and thus minimizes the occurrence of missing the edge of the scanned image data.

■Improved efficiency for pre-scan work

The scanner can perform "batch scanning" which allows you to scan documents with different paper weights and sizes at once, simplifying the process of sorting the documents before scanning.

■Reduced work loss caused by multifeeds

The scanner mounts an ultrasonic multifeeds sensor that accurately detects "multifeeds" errors where two or more sheets are fed through the scanner at once. This multifeeds detection is reliable even when scanning a mixed batch of documents with different paper weights and sizes, avoiding potential work loss.

■Intelligent Multifeed function

When there is paper of the same size attached to a designated location on the page, the Intelligent Multifeed function enables the scanner to recognize the location of the attachment. This allows you to continue scanning instead of pausing the scan by detecting every paper attachment as multifeed.

■Advanced image processing function

The scanner's automatic detection function outputs images in color or monochrome by the document content. This allows you to save the hassle of changing the settings for every scan.

■Centralized management of multiple scanners

The bundled "Scanner Central Admin" application allows you to manage multiple scanners together. For example, you can update the scanner settings and drivers, as well as monitor the operating status of each scanner.

■Renewed scanner driver and image capturing software

●PaperStream IP – produce high quality image processing

PaperStream IP is the scanner driver for fi Series which is based on TWAIN / ISIS standard. With the advanced black and white process, various documents can be automatically and easily converted into image data suitable for OCR (Optical character recognition). High quality image data can be created without pre-setting the scanning settings beforehand.

●PaperStream Capture – enhance batch scanning

PaperStream Capture is an application to scan and manage the scanned data using fi Series scanners. Whether it is adjusting the scanning settings or performing batch scanning, you can complete the tasks easily with the user-friendly UI. With the seamless linkage with PaperStream IP, you can perform high quality image processing and batch scanning at the same time.

■Option: Post Imprinter

The optional imprinter unit prints identification markers like dates, alphanumeric codes and symbols on reverse side of the original document. This makes it easier to locate the originals of scanned document when you need to reference them.

■Option: ScanSnap Carrier Sheets

Carrier Sheets allow you to scan documents, photos or clippings larger than A4 size. Documents larger than A4 (such as A3 or B4) or photos and clippings that can be damaged easily can be digitized when using the Carrier Sheets.

*ScanSnap Carrier Sheets (5 sheets per set) can be purchased separately. (The Carrier Sheet should be replaced approximately every 500 scans)

■Technical Specifications

Description		fi-7160
Supported operating systems		Windows® 8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows® XP (32-bit/64-bit), Windows Server® 2012, Windows Server® 2008 (32-bit/64-bit)
Scanner type		Automatic Document Feeder(ADF)
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome
Image sensor type		Color CCD (Charge-coupled device) x 2 (front x 1, back x 1)
Light source		White LED Array x 2 (front x 1, back x 1)
Multi-feed detection		Ultrasonic multi-feed detection sensor x 1, Paper detection sensor
Document size	Maximum	216 x 355.6 mm (8.5 x 14 in.)
	Minimum ^{*1}	50.8 x 54 mm (2 x 2.13 in.) (Landscape / Portrait)
	Long paper scanning (Maximum) ^{*2}	216 x 5,588 mm (8.5 x 220 in.)
Paper weight (Thickness) ^{*3}		27 to 413 g/m ² (7.2 to 112 lbs), 127 to 209 g/m ² (34 to 56 lb) for A8 size, 1.4 mm or less for plastic card ^{*4}
Scanning speed (A4, Portrait) ^{*5}	Color ^{*6}	Simplex: 60 ppm (200/300 dpi), Duplex: 120 ipm (200/300 dpi)
	Grayscale ^{*6}	
	Monochrome ^{*7}	
Paper chute capacity ^{*8}		80 sheets (A4: 80 g/m ² or 20 lb) (Active loadable ADF)
Expected daily volume		4,000 sheets / day
Background colors		White / Black (Selectable)
Optical resolution		600 dpi
Output resolution ^{*9}	Color (24-bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1200 dpi (driver) ^{*10}
	Grayscale (8-bit)	
	Monochrome (1-bit)	
Output format	Color	24-bit
	Grayscale	8-bit
	Monochrome	1-bit
Internal video processing		65,536 levels (16-bit)
Interface ^{*11}		USB3.0 (USB2.0 is also available)
Connector shape		B type
Image processing functions	Hardware-based	Dropout color (R, G, B), Deskew cropping
	Software-based	Multi-image, Auto color, Blank page skip, i-DTC, Advanced-DTC, Simplified-DTC, Error diffusion, Dither, Moire removal, Image emphasis, Color cleanup, Dropout color (None, Specified, Color saturation), sRGB, Punch hole removal, Tab cropping, Upper lower separation
Power requirements		AC 100 to 240 V ± 10%
Power consumption	Operating mode	38 W or less
	Sleep mode	1.8 W or less
	Auto Standby (Off) mode	0.35 W or less
Operating environment	Temperature	5 to 35 °C (42 to 95 °F)
	Relative humidity	20 to 80 % (Non-condensing)
Dimensions: Width x Depth x Height ^{*12}		300 x 170 x 163 mm (11.81 x 6.69 x 6.42 in.) Installation space: 400 x 700 x 380 mm (15.75 x 27.56 x 14.96 in.)
Weight		4.2 kg (9.26 lb)
Included software / drivers		PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series, Scan to Microsoft SharePoint, ABBYY FineReader for ScanSnap, Scanner Central Admin Agent
Environmental compliance		ENERGY STAR® and RoHS
Included items		ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM

*1 The minimum scanning area only applies to using the ADF. There is no limitation when using the flatbed.

*2 Can scan documents longer than A4 size. When using PaperStream IP (TWAIN/ISIS) to scan at 200 dpi, the maximum scanning length is 5,588 mm (220 in.).

*3 The paper weight only applies to using the ADF. There is no limitation when using the flatbed.

*4 Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.)

*5 Actual scanning speeds are affected by data transmission and software processing times.

*6 JPEG compressed figures.

*7 TIFF G4 compressed figures.

*8 Maximum capacity varies, depending upon paper weight.

*9 Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.

*10 Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600 dpi or higher).

*11 Connection with USB3.0 / 2.0 requires the USB port and the hub to support USB3.0 / 2.0. Also note that the scanning speed slows down when using USB1.1.

*12 Excluding the ADF paper chute and stacker.

■Options

Description	Parts number	Comments
Post Imprinter (fi-718PR)	PA03670-D201	Assists document management by printing numbers, Roman characters and codes on original documents after they have been scanned.
ScanSnap Carrier Sheets	PA03360-0013	Each package contains 5 carrier sheets. It is recommended that each carrier sheet be replaced after it has been used for 500 scans.

■Consumables

Description	Parts number	Comments
BRAKE ROLLER	PA03670-0001	Lifetime: Every 200,000 sheets or one year. These rollers separate documents as they are being fed into the scanner.
PICK ROLLER	PA03670-0002	Lifetime: Every 200,000 sheets or one year. These rollers feed documents into the scanner.
PRINT CARTRIDGE	CA00050-0262	Lifetime: 4,000,000 printed characters fi-718PR print head

■Trademarks

* ABBYY® FineReader™ Engine ©ABBYY. OCR by ABBYY ABBYY and FineReader are trademarks of ABBYY.

* ISIS is a registered trademark of EMC Corporation of the United States.

* Microsoft, Windows, Windows Server, Windows Vista and SharePoint are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

* Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

▲ Safety Precautions

- Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.
- Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
- Be sure to limit the use of this product to listed power ratings.



PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.